

**SPECIFICATION CLAUSE
SLABDRAIN H200KS - LOAD CLASS A-B**

GENERAL

THE SURFACE DRAINAGE SYSTEM SHALL BE ACO'S SLABDRAIN H200KS POLYMER CONCRETE SHALLOW CHANNEL SYSTEM WITH STAINLESS STEEL EDGE RAILS AS MANUFACTURED BY ACO.

MATERIALS

H200KS CHANNELS SHALL BE MANUFACTURED FROM POLYESTER RESIN POLYMER CONCRETE WITH INTEGRALLY CAST-IN STAINLESS STEEL EDGE RAILS. PROPERTIES OF POLYMER CONCRETE WILL BE AS FOLLOWS WITH SUPPORTING DOCUMENTATION:

| | |
|---------------------------------------|--------------------------------|
| COMPRESSIVE STRENGTH: | 98 MPa |
| FLEXURAL STRENGTH: | 26 MPa |
| TENSILE STRENGTH: | 14 MPa |
| WATER ABSORPTION: | 0.07% |
| FROST PROOF: | YES |
| COEFFICIENT OF EXPANSION/CONTRACTION: | 2.02x10⁻⁵/°C |
| WATER VAPOUR TRANSMISSION: | 0.0364g/m² |
| NON FLAMMABLE: | YES |
| COEFFICIENT OF ROUGHNESS (MANNINGS): | n=0.011 |
| RESISTANT TO WEATHERING: | YES |
| DILUTE ACID AND ALKALI RESISTANT: | YES |
| SF SEALANT GROOVE | YES |

CHANNELS


H200KS CHANNEL SHALL BE 200mm NOMINAL INTERNAL WIDTH WITH AN OVERALL WIDTH OF 250mm. CHANNELS SHALL HAVE AN OVERALL DEPTH OF 130mm FOR USE IN AREAS WITH DEPTH RESTRICTIONS. ALL CHANNELS SHALL BE INTERLOCKING WITH A MALE/FEMALE JOINT.

GRATES

INSERT SPECIFICATION FOR THE SELECTED GRATE. REFER TO THE RELEVANT ACO SPECIFICATION INFORMATION SHEET.
CLICK: www.acodrain.com.au/resources

INSTALLATION

THE COMPLETE DRAINAGE SYSTEM SHALL BE BY ACO AND TO BE INSTALLED FOR ITS INTENDED PURPOSE. ANY DEVIATION OR PARTIAL USE OF THE SPECIFIED SYSTEM AND/OR IMPROPER INSTALLATION WILL VOID ALL WARRANTIES PROVIDED BY ACO.



NOTES:

1. Specific site conditions may require an increase in concrete encasement dimensions and/or reinforcement. It is the customer's responsibility to ensure the concrete encasement is designed for the application. A minimum concrete strength of 25MPa is recommended. The concrete should be vibrated to eliminate air pockets. *Engineering advice may be required.*
2. The finished level of the concrete must be approximately 3mm above the top of the channel edge.
3. The finished level of the soil to match that of the concrete encasement.
4. For further details, refer to ACO's design & site installation files at www.acodrain.com.au/resources

H2KS-AB-G

**H200KS - SLABDRAIN - LOAD CLASS: A-B
FOR GRASS**



DATE: 12/13

INSTALLATION DRAWING - ACO DRAIN

ACO Polycrete Pty Ltd
Australia
Ph: 1300 765 226
www.acodrain.com.au

ACO Limited
New Zealand
Ph: 0800 448 080
www.acodrain.co.nz